

design conditions stipulate that the low emissivity side should face the hotter place. How would the shield temperature be affected if during installation, a mistake occurs and the higher emissivity side is placed facing the hot place? (15)

7. Write short notes on :

- (a) Modes of mass transfer. (8)
(b) Fick's law. (7)
-

Roll No.

Total Pages : 4

013614

August/September 2022

**B.Tech. (ME) Re-Appear VI SEMESTER
Heat and Mass Transfer (ME-302C)**

Time : 3 Hours]

[Max. Marks : 75

Instructions :

- 1. It is compulsory to answer all the questions (1.5 marks each) of Part-A in short.*
- 2. Answer any four questions from Part-B in detail.*
- 3. Different sub-parts of a question are to be attempted adjacent to each other.*

PART-A

1. (a) State Fourier's Law of heat conduction. (1.5)

(b) An oil cooler in a high performance engine has an outside surface area 0.12 m^2 and a surface temperature of 70°C . The air rushes flows over the cooler surface at a temperature of 35°C and gives rise to a surface coefficient of heat transfer equal to $45.4 \text{ W/m}^2\text{K}$. Calculate heat transfer rate from the cooler. (1.5)

(c) What is meant by critical thickness of insulation? (1.5)

- (d) Define the term effectiveness of fin. (1.5)
- (e) Define Nusselt and Grashof number. (1.5)
- (f) What do you understand by nucleation in nucleate boiling? (1.5)
- (g) Define effectiveness and NTU of a heat exchanger. (1.5)
- (h) State Kirchhoff's law. (1.5)
- (i) Explain the terms absorptivity, reflectivity and transmissivity of radiant energy. (1.5)
- (j) Distinguish between molecular diffusion and eddy diffusion. (1.5)

PART-B

2. (a) State and explain Stefan Boltzman law relating to thermal radiation and temperature of a radiating body. (10)
- (b) Define thermal diffusivity and explain its physical significance. (5)
3. A spherical tank of 3 m internal diameter and made of 2 cm thick stainless steel ($k = 15 \text{ W/m-deg}$) is used to store ice water at 0°C . The tank loses heat to surrounding at 25°C by natural convection and radiation with a combined heat transfer coefficient of $15.5 \text{ W/m}^2\text{-deg}$. If the convective coefficient at the inner surface of the tank is $80 \text{ W/m}^2\text{-deg}$, determine :

- (i) the rate of heat transfer to the iced water in the tank, and
- (ii) the amount of ice that melts during a period of 24 hours (latent heat of ice = 334 kJ/kg). (15)
4. Establish the expression for log-mean temperature difference (LMTD) for a (i) parallel flow and a (ii) counter flow heat exchanger. (15)
5. (a) How does filmwise condensation differ from dropwise condensation? Which type has a higher heat transfer film coefficient and why? (5)
- (b) A heat-treat steel plate measures $3 \text{ m} \times 1 \text{ m}$ and is initially at 30°C . It is cooled by blowing air parallel to 1 m edge at 9 km/hr . If the air is at 10°C , calculate the convective heat transfer from both sides of the plate. (At the mean film temperature 20°C , the thermo-physical properties of air are: kinematic viscosity = $15.06 \times 10^{-6} \text{ m}^2/\text{s}$; thermal conductivity = 0.0259 W/m-deg ; $\text{Pr} = 0.703$. (10)
6. Two large parallel planes with emissivity 0.8 are exchanging heat by radiation. One plane has a temperature of 1000 K while the other plane is at 400 K temperature. It is then proposed to interpose a radiation shield with emissivity value of 0.05 on one side and 0.6 on the other side. The